

## Product-Specification

Product	CUBE 100			
Product-Number	C3O-L00100	C3S-D00100	Unit	Tolerance
Position-Sensor	-	SGS		
Range (0..150 V)	75	75	μm	±10%
Range (-45..180 V)	120	120	μm	±10%
Range, closed loop	-	100	μm	±0.2%
Resolution, open loop	0.5	0.5	nm	typ.
Resolution, closed loop	-	1	nm	typ.
Linearity, closed loop	-	0.2	%	max.
Repeatability, closed loop	-	10	nm	typ.
Load	500		g	max.
Push/Pull	15/10		N	max.
Stiffness	1.5		N/μm	±10%
Lowest Resonance, unloaded	370		Hz	±10%
Lowest Resonance, w/ load 30g	310		Hz	±10%
El. Capacitance @ 1V eff. 1kHz	2.2/axis		μF	±10%
Body-Material	aluminum, stainless steel			
Dimensions	40x40x44.6		mm	
Wire-Length	1.5		m	
Connectors	Lemosa	DSub		
Operating Temperature	-20..+80		°C	

### Options:

- Vacuum-Compatibility and/or Non-Magnetic
- Suitable drivers, open-loop, EBO-050100
- Suitable controllers, closed-loop, EBD-120230

